

## Acer Altos G330 Mk2

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- Betaalbare, instapniveau serveroplossing
- Best in class upgrademogelijkheden
- Best in class redundantieoplossingen met RAID 0,1,10 ondersteuning
- Best in class prestaties met ondersteuning van Quad-Core technologie
- Uitgebreide systeembeheer en installatie oplossingen beschikbaar

**Standaardconfiguratie**

Form Factor	Tower
Processor	Dual or Quad Core Intel® Xeon® 3000, 3100, 3200, 3300 sequences Intel® Core™2 Duo processor, Intel® Core™2 Quad processor, Intel® Pentium® dual-core processor Quad-core processors supported Front-side bus: 800/1066/1333 MHz Supporting: - Intel® Virtualization Technology - Intel® Hyper-Threading™ Technology (Different processors support different features and different cache sizes.) - Intel®EM64T - Enhanced Intel® SpeedStep® Technology
Number of processors (Std/Max)	1 (1/1)
Memory (Std/Max)	Four Unbuffered DDR2 800 ECC DIMMs Dual-channel memory bus 1GB or 2 GB DIMMs for up to 8 GB of total system memory
Expansion slots	One PCI Express® x16 slot (x8 throughput) VGA card not supported One PCI Express® x8 slot (x4 throughput) One PCI Express® x4 slot (x1 throughput) Two 32-bit, 33 MHz (3.3 V) PCI slots
Storage Interface	Integrated 6-port SATA software with RAID 0, 1, 10 support
Disk Bays	Up to four SATA or SAS HDDs on Acer Carrier Optional hot-swap HDD backplane kit Three 5.25" half-height device bays (2 Free)
Max Internal Storage	3TB SATA (4 750GB SATA HDD) 1.2TB SAS (4 300GB SAS drives)
Network Interface	Integrated single Gigabit Ethernet
System Power Supply	350 W ATX 12 V auto-switching PFC power supply
Hot Swap Components	Optional Hot Swap Hard Disk upgrade kit
Systems Management	Acer Altos Easybuild included Acer Altos Advanced Server Manager optional
Floppy and CD	Optional Floppy kit DVD
Cooling system	System fan
Operating systems supported	Microsoft® Windows® Server 2003 Enterprise x64 Edition Microsoft® Windows® Server 2003 Enterprise Edition Microsoft® Windows® Server 2003 Standard x64 Edition Microsoft® Windows® Server 2003 Standard Edition Microsoft® Windows® Small Business Server 2003, Standard Edition Microsoft® Windows® Small Business Server 2003, Premium Edition Red Hat® Enterprise Linux 5.0 (EM64T) Red Hat® Enterprise Linux 5.0 Novell® SUSE® Linux Enterprise Server 10 (EM64T) Novell® SUSE® Linux Enterprise Server 10
Safety	UL/cUL, Nemko CB/ GS, CE, CCC
EMI	FCC, CE, BSMI, CCC
Weight	13.4 kg System weight varies according to configuration. The weight quoted is for a typical configuration.
Dimensions	424.6 (H) x 185.9 (W) x 479.7 (D) mm
Security features	Chassis intrusion alert Lockable Door
On-board I/O connectors	Two PS/2 ports Four USB 2.0 ports (two front accessible) One serial port One Ethernet (RJ-45) port One VGA port

Model	Artikelnummer	Prijs inc. BTW	
<b>Altos G330 Mk2</b> Altos G330Mk2 PDC E2220 2,4GHZ/800FSB/1MB, 1x1GB DDR II 800, DVD, 2x250GB SATA HDD (Internal), HDD fan, NO FDD, EURO power cable, PS2 Mouse, no KB, 1xLAN Gbit onboard, EasyBuild 8.0, no ASM, 1 Year On-Site + 2 Year Carry-In Warranty NBD	TT.G3BE0.HS5	EUR 506.00	
<b>Altos G330 Mk2</b> Altos G330Mk2 SAS Xeon DC E3110 3.00GHZ/1333FSB/6MB, 1GB DDR II 800, DVD, SAS controller 4 port (SO.SA000.A02 support RAID 5 SW, Windows and Linux), SAS/SATA Hot Swap backplane kit (SO.G33SA.005), NO HDD, NO FDD, EURO power cable, PS2 Mouse, 1xLAN Gbit onboard, NO KB, EasyBuild 8.0, no ASM, 1 Year On-Site + 2 Year Carry-In Warranty NBD	TT.G3BE0.HS2	EUR 855.00	
<b>Altos G330 Mk2</b> Altos G330Mk2 PDC E2220 2,4GHZ/800FSB/1MB, 1GB DDR II 800, DVD, NO HDD, NO FDD, EURO power cable, PS2 Mouse, 1xLAN Gbit onboard, NO KB, EasyBuild 8.0, no ASM, 1 Year On-Site + 2 Year Carry-In Warranty NBD	TT.G3BE0.004	EUR 361.00	
<b>Altos G330 Mk2</b> Altos G330Mk2 Xeon QC X3330 2.66GHZ/1333FSB/6MB, 1GB DDR II 800, DVD, NO HDD, NO FDD, EURO power cable, PS2 Mouse, 1xLAN Gbit onboard, NO KB, EasyBuild 8.0, no ASM, 1 Year On-Site + 2 Year Carry-In Warranty NBD	TT.G3BE0.023	EUR 623.00	
<b>Acer Garantie Uitbreiding</b> warranty 3Yon-site nbd G3xx	SV.WSVAF.E01	EUR 144.00	

## Acer Altos G540

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- Baanbrekende technologie workgroup server met 64-bit Dual Core Processing-technologie
- Flexibel en modulair ontwerp
- Best in klasse redundantie oplossingen
- Best in klasse prestaties
- Uitgebreide oplossingen systeembeheer en installatie

**Standaardconfiguratie**

Form Factor	Tower, Rack/5U
Processor	One or two 64-bit Dual-Core Intel® Xeon® processor 5000 sequence: o Up to 3.73 GHz with 2x2 MB L2 cache o Up to 3 GHz with 4 MB L2 cache o Front-side bus: 1066/1333 MHz Intel® EM64T Intel® Virtualization Technology Intel® Hyper-Threading™ Technology Enhanced Intel SpeedStep® Technology (EIST) support
Number of processors (Std/Max)	1/2
Memory (Std/Max)	Eight Fully Buffered DDR2 667 ECC registered DIMMs o Quad-channel memory bus o Memory mirroring o Memory sparing 1GB to 4 GB DIMMs for up to 32 GB of total system memory¹
Expansion slots	Three PCI Express™ x8 slots Two 64-bit/66 or 100 MHz PCI-X® slots One 32-bit 33 MHz PCI slot
Storage Interface	Six SATA 3 Gb/s ports onboard Optional U320 SCSI PCI-X® add-on card supports SCSI Tape Backup Devices Optional 8 Port SAS
Disk Bays	8 SATA or SAS disks EZSwap or Hot Swap 8 SATA or SAS Hotswap option, in two Cage Bays 3.525" bays
Max Internal Storage	4.0TB SATA (8 500GB SATA drives) 2.4TB SCSI (8 300GB SAS drives)
Network Interface	Dual Integrated 10/100/1000 Ethernet Intel® I/O Acceleration Technology
System Power Supply (Std/Max)	610W Redundant Switching Power Supply (1/2)
Hot Swap Components	Optional Hard Disk Drives Redundant Power Supply Optional Hot Swap Redundant Fan
Systems Management	Acer Altos Easybuild Acer Altos Advanced Server Manager v7.1 Acer Altos Remote Management Card option kit
Floppy and CD	Floppy included 5.25" DVD Reader
Cooling system	Redundant Hot Swap Fan Option
Operating systems supported	Windows® Server 2003 Enterprise x64 Edition Windows® Server 2003 Standard Edition Windows® Server 2003 Enterprise Edition Windows® Server 2003 Standard x64 SUSE Linux Enterprise Server 9 Red Hat Enterprise Linux 4.0 (EM64T) SUSE Linux Enterprise Server 9 (EM64T)Edition Red Hat Enterprise Linux 4.0 Novell® NetWare® 6.5
Safety	UL, Nemko GS, CB
EMI	FCC Class B, BSMI, CCC, CE
Weight	32 kg Note - weights vary according to configuration
Dimensions	445 (H) x 212 (W) x 550 (D) mm
Security features	Acer Altos Easydiagnostics o Power status LED o HDD access LED o LAN activity LED o System Status LED Chassis intrusion alert Lockable side panel

On-board I/O connectors	Two PS/2 ports Parallel port Serial port Six USB 2.0 ports (two front-accessible) Two Ethernet (RJ-45) ports VGA port
Options and accessories	64-bit Dual-Core Intel® Xeon® processor 5000 sequence: . 3 - 3.73 GHz with 2x2 MB L2 cache . 1.6 - 3 GHz with 4 MB L2 cach Memory: . Fully Buffered DDR2 533/667 ECC DIMMs: 512 MB, 1 or 2 GB HDD: . 73, 146, 300 GB (10,000 rpm) SAS HDD . 36, 73, 146 GB (15,000 rpm) SAS HDD . 160/250/320/400/500 GB (7,200 rpm) SATA 2 HDD Daughter cards/modules: . 8-port SAS daughter card . IPMI module . Acer Remote Management Card (ARMC/3) Add-on cards: . Zero-channel SAS RAID PCI-X® add-on card . ASC/3S single-channel U320 SCSI HBA (for backup device) . AFC/2S single-port 2Gb FC HBA . ASC/3D dual-channel U320 SCSI HBA (for backup device) . AFC/4S single-port 4Gb FC HBA . AFC/4D dual-port 4Gb FC HBA . Gigabit Ethernet server adapter Storage drives: . Acer AIT-1 Turbo 40/104 GB SATA tape drive . Acer DAT72 36/72 GB SCSI tape drive . DVD-RW or DVD/CD-RW . Acer AIT-2 Turbo 80/208 GB SCSI tape drive . Acer LTO Ultrium-2 SCSI tape drive . Acer LTO Ultrium-3 SCSI tape drive Altos rack mount kit Redundant Hot Swap fan module 610 W hot-swappable, redundant power supply module

Model	Artikelnummer	Prijs inc. BTW	
<b>Altos G540</b> Altos G540 Xeon QC E5405 2.0GHz/1333 MHz/12MB, 2x1GB FBD 667, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, 2x 500GB SATA HDD, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.G54E0.HS6	EUR 1232.00	
<b>Altos G540</b> Altos G540 SAS Xeon QC E5405 2.0GHz/1333 MHz/12MB, 2x1GB FBD 667, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, PCI SAS RAID 5/6 Controller 256MB cache (SO.SA256.A01), NO HDD, DVD, 2xLAN gigabit onboard, BMC managment module (SO.BMCG5.002), Redundant Fan (SO.G54FK.001), EURO power cable, PS2 mouse, NO KB, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.G54E0.HS7	EUR 1595.00	
<b>Altos G540</b> Altos G540 Xeon DC E5205 1.83GHz/1066 MHz/6MB, 1x1GB FBD 667, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, no HDD, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.G54E0.030	EUR 1014.00	
<b>Altos G540</b> Altos G540 Xeon QC E5405 2.0GHz/1333 MHz/12MB, 2x1GB FBD 667, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, no HDD, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.G54E0.033	EUR 1160.00	
<b>Acer Garantie Uitbreiding</b> warranty 3Y on-site 4H onsite G5xx/R3xx/R5xx (mon-fri. 09:00-18:00, call before 14:00, if later than 14:00 onsite next business morning)	SV.WSVAF.E04	EUR 521.00	

## Acer Altos G5450

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- Toonaangevende technologie workgroup server met 64-bit Processingtechnologie
- Quad-Core processor ondersteuning met Hypertransport™ technologie
- Flexibel en modulair ontwerp
- 'Best in class' redundantie oplossingen
- 'Best in class' prestaties
- Uitgebreide systeembeheer- en installatieoplossingen

**Standaardconfiguratie**

Form Factor	Tower, Rack 5U with optional rack kit
Processor	One or two AMD Opteron™ 2000 series dual-core processors or AMD Opteron™ 2000 series quad-core processors (when available) AMD virtualization technology (AMD-V) Integrated memory controller Simultaneous 32-bit and 64-bit computing (AMD64 technology) AMD PowerNow!™ Technology AMD HyperTransport™ technology Enhanced Virus Protection (EVP)
Number of processors (Std/Max)	1 / 2
Memory (Std/Max)	Sixteen DDR2 667 registered ECC SDRAM DIMM slots 512 MB to 4 GB DIMMs, supporting up to 64 GB of system memory (when 4GB modules available) Single-processor supports memory capacity of 32GB (when 4GB modules available) Dual-processor supports memory capacity of 64GB (when 4GB modules available) Dual channel support per processor Support Memory Sparing Technology
Expansion slots	5 total standard PCI slots One PCI-Express x16Slot with x16 throughput One PCI-Express x16 slot with x8 throughput One PCI-Express x8 slot with x4 throughput Two 32-bit/33 MHz 3,3V PCI Bus Slots
Storage Interface	Integrated 6-port SATA2 onboard Integrated SATA S/W RAID 0, 1, 5, 10 Optional add-on SAS HBA or SAS RAID card
Disk Bays	up to 8 SATA or SAS disks two cages supporting 4 HDD each. Second cage optional 3x 5.25" bay
Max Internal Storage	6.0TB SATA (8 750GB SATA drives) 2.4TB SAS (8 300GB SAS drives)
Network Interface	Integrated dual-port gigabit Ethernet with TCP Offload Engine
System Power Supply (Std/Max)	610W Redundant Switching Power Supply (1/2)
Hot Swap Components	Optional Hard Disk Drives Optional Redundant Power Supply Optional Hot Swap Redundant Fan
Systems Management and Applications	Acer Altos Easybuild  Acer Altos Advanced Server Manager v7.1 Acer Altos Remote Management Card option kit Acer eBusiness Value Pack (optional) Acer eBusiness ValueSTOR (optional)
Floppy and CD	3.5" Floppy Disk Drive optional (takes 1 5,25" bay) 5.25" DVD Reader
Cooling system	Optional second redundant fan Optional Redundant and Hot Swap Fan Kit
Operating systems supported	Microsoft® Windows Server™ 2003 Enterprise Edition Microsoft® Windows Server™ 2003 Enterprise Edition x64 Red Hat® Enterprise Linux® Advanced Server 4.0 Red Hat® Enterprise Linux® Advanced Server 4.0 x64 SUSE® Linux Enterprise Server 10 SUSE® Linux Enterprise Server 10 x64

Safety	UL/cUL, CB, BSMI, Memko-GS
EMI	FCC Class B, BSMI, CE
Weight	System weight will vary according to configuration. Typical configuration weight is 26KG
Dimensions	445 (H) x 212 (W) x 550 (D) mm
Security features	Acer Altos Easydiagnostics: - Power status LED - HDD access LED - LAN activity LED - System Status LED Chassis intrusion alert Lockable side panel
On-board I/O connectors	Two PS/2 ports (Mouse/Keyboard) Four USB 2.0 ports (two front accessible, four rear) One DB9 serial port One VGA port Two gigabit Ethernet LAN ports (RJ-45)
VGA	Integrated XGI Z9s with 16 MB of SDRAM ATI FireGL™ V5200 with Avivo™ Technology (optional)
Options and accessories	DDR2 667 registered ECC DIMM modules: 512 MB / 1 GB / 2 GB / 4 GB (when available) 73/146/300 GB (10,000 or 15,000 rpm) SAS HDD 80/250/500/750 GB (7,200 rpm) SATA 3 Gb/s HDD BMC module PMI 2.0 Acer Remote Management Card (ARMC/3P) single-channel U320 SCSI HBA for tape drives four-channel SAS HBA eight-channel SAS RAID single/dual port 4 Gb FC HBA Single/dual Gigabit Ethernet server adapter ATI FireGL™ V5200 with Avivo™ Technology Acer AIT-1 Turbo 40/104 GB SATA tape drive Acer AIT-2 Turbo 80/208 GB SATA/SCSI tape drive Acer DAT72 36/72 GB SATA/SCSI tape drive Acer LTO Ultrium-2 200/400 GB SCSI tape drive Acer LTO Ultrium-3 400/800 GB SCSI tape drive DVD-RW 3.5"1.44 MB FDD with 5.25"drive bay conversion kit Secondary 610 W hot-swappable, redundant power supply module Secondary redundant system fan module Hot-swappable 1+1 redundant system fan kit Altos rack mount kit

Model	Artikelnummer	Prijs inc. BTW	
<b>Altos G5450 Server</b> Altos G5450 1x AMD Opteron DC 2212 2.0GHz/2x1MB, 2x1GB DDR2, 16x DVD, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, 2x500GB SATA, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild 7.1, 3 Year Warranty On Site Next Business Day	TT.G5AE0.HS1	EUR 1232.00	
<b>Altos G5450</b> Altos G5450 Opteron QC 2376 2.3GHz/6M, 2x1GB DDR2, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, 2X640GB HDD, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.G5AE0.HS2	EUR 1450.00	
<b>Altos G5450 Server</b> Altos G5450 1x AMD Opteron DC 2212 2.0GHz/2x1MB, 1x1GB DDR2, 16x DVD, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, no HDD, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild 7.1, 3 Year Warranty On Site Next Business Day	TT.G5AE0.002	EUR 985.00	
<b>Altos G5450</b> Altos G5450 Opteron B3 QC 2344HE 1.7GHz, 2x1GB DDR2, 16x DVD, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, no HDD, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.G5AE0.029	EUR 1014.00	
<b>Altos G5450</b> Altos G5450 Opteron QC 2376 2.3GHz/6M, 2x1GB DDR2, 1xSAS/SATA HDD cage (4 bays, second cage optional), SATA 6 ch on board, no HDD, DVD, 2xLAN gigabit onboard, EURO power cable, PS2 mouse, NO KB, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.G5AE0.053	EUR 1305.00	
<b>Acer Garantie Uitbreiding</b> warranty 3Y on-site 4H onsite G5xx/R3xx/R5xx (mon-fri. 09:00-18:00, call before 14:00, if later than 14:00 onsite next business morning)	SV.WSVAF.E04	EUR 521.00	

## Acer Altos R520

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- High-density server 1U form factor
- Hoge-beschikbaarheidsoplossing
- Best in class prestaties met Dual Intel Xeon-processoren
- Tool-less design voor hoogste servicemogelijkheden en uitbreidbaarheid
- Uitvoerig systeembeheer en installatie oplossingen

**Standaardconfiguratie**

Form Factor	1U rack mount
Processor	One or two 64-bit Quad-Core or Dual-Core Intel® Xeon® Processor 5000 sequence: - Up to 3.73 GHz with 2x 2 MB L2 cache - Up to 3 GHz with 4 MB L2 cache - Up to 2.66 GHz with 2x 4 MB L2 cache Front-side bus: 1066/1333 MHz - Intel® Virtualization Technology - Hyper-Threading Technology - Intel® EM64T
Number of processors (Std/Max)	1/2
Cache (Max)	4MB L2 (8MB L2)
Memory (Std/Max)	Eight Fully Buffered DDR2 667 ECC registered DIMMs supporting: Quad-channel memory bus 512 MB to 4 GB DIMMs for up to 32 GB of total system memory*** Memory mirroring Memory sparing
Expansion slots	2 PCI Slots available 1 low profile PCI Express X8 1 high profile PCI Express X8 changeable to PCI-X slot
Storage Interface	6 Channel integrated SATA controller
Disk Bays	Up to eight SAS/SATA HDDs
Max Internal Storage	Up to eight SAS HDDs for a total of 1.168 TB of storage Up to eight SATA HDDs for a total of 1.28 TB of storage
Network Interface	Integrated dual-port Gigabit Ethernet
Hot Swap Components	Hotswap Hard Drives, Hotswap redundant Power Supplies and Easyswap fans
RAID Support	Supports hot-plug SATA with 6 Channel SATA controller installed Integrated SATA S/W RAID with RAID level 0, 1, 10 supported Optional SATA S/W RAID 5 Supports hot-plug SAS/SATA with optional SAS upgrade kit installed Integrated SAS S/W RAID with RAID level 0, 1, 10 supported Optional SAS H/W RAID with RAID level 0, 1, 5, 6, 10, 50 supported
Systems Management	Acer Altos Advanced Server Manager v7.1 Acer Altos Easybuild v7.1
Floppy and CD	Slim-type DVD combo or DVD writer drive (optional) Optional floppy
Cooling system	Up to five easy-swap system fans
Operating systems supported	Windows Server® 2003 Standard x64 Edition Windows Server® 2003 Standard Edition Red Hat Enterprise Linux 4.0 (EM64T) Red Hat Enterprise Linux 4.0 SUSE Linux Enterprise Server 9 (EM64T) SUSE Linux Enterprise Server 9 Novell® NetWare® 6.5
Safety	UL/cUL, Nemko GS, CB, CCC
EMI (Class A)	FCC, CE, BSMI, CCC
Weight	16.8 kg (max)
Dimensions	43.2 (H) x 430 (W) x 654.4 (D) mm
On-board I/O connectors	Two PS/2 ports (rear) ; Three USB ports (2 rear, 1 front) ; One serial port (RJ-45, rear) ; One VGA port (rear) ; Two network ports (RJ-45, rear)

Model	Artikelnummer	Prijs inc. BTW	
<b>Altos R520</b> Altos R520, Rack 1U, Xeon QC E5405 2.0GHz/1333 MHz/12MB, 2x1GB FBD 667, SATA 6ch on board (SW RAID 0,1,10), DVD Writer Supermulti (slim), 2x80GB HDD (2,5"hot swap), EURO power cable, 2x LAN gigabit on board, NO rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Years On-Site NBD Warranty	TT.R52E0.HS4	EUR 1522.00	
<b>Altos R520</b> Altos R520, Rack 1U, Xeon QC E5420 2.50GHz/1333 MHz/12MB, 2x1GB FBD 667, SATA 6ch on board (SW RAID 0,1,10), no DVD, no HDD, EURO power cable, 2x LAN gigabit on board, NO rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Years On-Site NBD Warranty	TT.R52E0.035	EUR 1522.00	
<b>Acer Garantie Uitbreiding</b> warranty 3Yon-site 4H onsite G5xx/R3xx/R5xx (mon-fri. 09:00-18:00, call before 14:00, if later than 14:00 onsite next business morning)	SV.WSVAF.E04	EUR 521.00	

## Acer Altos R5250

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- High density server 1U form factor
- High-performance cluster en Web Farm oplossing
- Best in class prestaties met Dual Opteron-processoren
- Uitgebreide systeembeheer- en installatie oplossingen

**Standaardconfiguratie**

Form Factor	1U rack mount
Processor	One or two quad-core or dual-core AMD Opteron™ 2000 Series processors, supporting: Direct Connect Architecture HyperTransport™ Technology Integrated memory controller AMD64 technology AMD PowerNow!™ Technology with OPM AMD Virtualization™ (AMD-V) technology Enhanced Virus Protection AMD CoolCore™ Technology Dual Dynamic Power Management™ (DDPM)
Number of processors (Std/Max)	1/2
Cache (Max)	Opteron Dual-core 2200 family: 2x 512 KB L2, 2 MB L3 cache Opteron Quad-core 2300 family: 4x 512 KB L2, 2 MB L3 cache
Memory (Std/Max)	16 DDR2 667 ECC registered DIMMs, supporting: Quad-channel memory bus (with two CPUs installed) 1 to 4 GB DIMMs for up to 64 GB (with two CPUs installed) of total system memory, when 4GB module will be available Memory sparing
Expansion slots	One PCI Express® x16 slot (default) or one PCI-X slot (with optional riser card) One PCI Express® x8 slot dedicated to either SAS or SAS RAID daughter board. No other card can use this slot
Storage Interface and RAID support	On board SATA controller with SW RAID 0,1,5 support (Windows and Linux) Optional SAS daughter card without iButton SW RAID 0,1 support (Windows and Linux) Optional SAS daughter card with iButton SW RAID 0,1,5 support (Windows and Linux)
Disk Bays	Up to three hot-plug SAS/SATA HDDs Slim-type bay for optional DVD reader or DVD-Super Multi
Max Internal Storage	Up to three 300GB SAS HDDs for a total of 0.9 TB of storage Up to three 750GB SATA HDDs for a total of 2,25 TB of storage
Network Interface	Integrated dual-port Gigabit Ethernet, supporting TCP Offload Engine (TOE)
Power Supply	650 W fixed power supply
Hot Swap Components	Hotswap Hard Drives
Systems Management	Acer Altos Advanced Server Manager v 8.0 Acer Altos Easybuild v 8.0 Optional BMC module Optional Acer Remote Management Card 3P
Floppy and DVD	Optional slimline DVD reader or Optional slimline DVD writer Optional external USB FDD 3,5"
Cooling system	Six easySwap active fans
Operating systems supported	Microsoft® Windows Server® 2003 Enterprise Edition(32 or 64-bit ) Microsoft® Windows Server® 2003 Standard Edition Red Hat® Enterprise Linux Advanced Server 5.0 (EM64T) Red Hat® Enterprise Linux Advanced Server 5.0 SUSE® Linux Enterprise Server 10 (EM64T) SUSE® Linux Enterprise Server 10
Safety	UL/cUL, Nemko GS, CE
EMI (Class A)	FCC, CE, BSMI
Weight	16.8 kg System weight varies according to configuration. The weight quoted is for a typical configuration
Dimensions	43.2 (H) x 430.2 (W) x 677.6 (D) mm
On-board I/O connectors	Two PS/2 ports One serial port Four USB 2.0 ports (two front accessible) Two Gigabit Ethernet (RJ-45) ports One VGA port

Model	Artikelnummer	Prijs inc. BTW	
<b>Altos R5250</b> Altos R5250, Rack 1U, Opteron DC 2212 2.0GHz/2x1MB, 2x1GB DDR2, SATA 6ch on board (SW RAID 0,1,10), 2x250GB SATA HDD, HDD HotPlug Backplane, no HDD, DVD Writer Supermulti (slim), EURO power cable, 2x LAN gigabit on board, NO rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Years On-Site NBD Warranty	TT.R5AE0.HS1	EUR 1305.00	
<b>Altos R5250</b> Altos R5250, Rack 1U, Opteron QC 2376 2.3GHz/6M, 2x1GB DDR2, SATA 6ch on board (SW RAID 0,1,10), HDD HotPlug Backplane, 2x640GB HDD, DVD Writer Supermulti, EURO power cable, 2x LAN gigabit on board, NO rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Years On-Site NBD Warranty	TT.R5AE0.HS2	EUR 1595.00	
<b>Altos R5250</b> Altos R5250, Rack 1U, Opteron B3 QC 2344HE 1.7GHz, 2x1GB DDR2, SATA 6ch on board (SW RAID 0,1,10), HDD HotPlug Backplane, no HDD, no DVD, EURO power cable, 2x LAN gigabit on board, NO rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Years On-Site NBD Warranty	TT.R5AE0.029	EUR 1160.00	
<b>Altos R5250</b> Altos R5250, Rack 1U, Opteron QC 2376 2.3GHz/6M, 2x1GB DDR2, SATA 6ch on board (SW RAID 0,1,10), HDD HotPlug Backplane, no HDD, no DVD, EURO power cable, 2x LAN gigabit on board, NO rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Years On-Site NBD Warranty	TT.R5AE0.053	EUR 1450.00	
<b>Acer Garantie Uitbreiding</b> warranty 3Yon-site 4H onsite G5xx/R3xx/R5xx (mon-fri. 09:00-18:00, call before 14:00, if later than 14:00 onsite next business morning)	SV.WSVAF.E04	EUR 521.00	

## Acer Altos R720

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- High density server 2U form factor
- Hoogwaardige rack-geoptimaliseerde applicatieserver met ondersteuning voor Dual Core 64-bit processor-technologie en SAS-technologie
- Grootste interne uitbreidingsmogelijkheden in klasse
- Gereedschapsloos ontwerp voor hoogste servicemogelijkheden
- Uitgebreide oplossingen systeembeheer en installatie

**Standaardconfiguratie**

Form Factor	Rack optimized 2U
Processor	One or two 64-bit Dual-Core Intel® Xeon® processor 5000 sequence: - Up to 3.73 GHz with 2x2 MB L2 cache - Up to 3 GHz with 4 MB L2 cache - Front-side bus: 1066/1333 MH Intel® EM64T Intel® Virtualization Technology Intel® Hyper-Threading™ Technology Enhanced Intel SpeedStep® Technology (EIST) support
Number of processors	1/2
Cache (Max)	Up to 3.73 GHz with 2x2 MB L2 cache Up to 3 GHz with 4 MB L2 cache
Memory (Std/Max)	Eight Fully Buffered DDR2 667 ECC registered DIMMs - Quad-channel memory bus - Memory mirroring - Memory sparing 1GB to 2 GB2 DIMMs for up to 16 GB of total system memory (when 4GB module will be available)
Expansion slots	Two PCI riser cards supported Low-profile riser card: Two PCI Express® X8 slots Full-height riser card: - Two PCI Express® X8 slots (X4/X8 throughput) and one 64-bit/133 MHz PCI-X slot (default) - Three 64-bit/66, 100 or 133 MHz PCI-X slots (optional) - Three 64-bit/133 MHz PCI-X slots (optional)
Storage Interface	Integrated SAS RAID controller with RAID level 0, 1, 5, 10 and 50 supported
Disk Bays	Up to six SAS/SATA HDDs (6th HDD tray upgrade kit optional) Slim-type 3.5" FDD (optional) Slim-type DVD Combo or DVD Writer drive (optional) SCSI or SATA tape drive (optional)
Max Internal Storage	3.0TB SATA (6 500GB SATA drives) 1.8TB SCSI (6 300GB SCSI drives)
Network Interface	Integrated dual-port gigabit Ethernet Intel® I/O Acceleration Technology
System Power Supply (Std/Max)	750 W 1+1 hot-swap, redundant power supply 110/220 V (1/2)
Hot Swap Components	Optional Hard Disk Drives Redundant Power Supply Hotswap Redundant Fans (5+1 Redundancy)
RAID Support	Integrated SAS RAID controller with RAID level 0, 1, 5, 10 and 50 supported
Systems Management	Acer Altos Easybuild Acer Altos Advanced Server Manager v7.1 Acer Altos Remote Management Card option kit
Floppy and CD	DVD reader and CDRW Combo Optional floppy
Cooling system	Up to six fans (three default), with hot-swap, 5+1 redundancy3
Operating systems supported	Windows® Server 2003 Enterprise x64 Edition Windows® Server 2003 Enterprise Edition Windows® Server 2003 Standard x64 Edition Windows® Server 2003 Standard Edition Red Hat Enterprise Linux 4.0 (EM64T) Red Hat Enterprise Linux 4.0 SUSE Linux Enterprise Server 9 (EM64T) SUSE Linux Enterprise Server 9 Novell® NetWare® 6.5
Safety	UL/cUL, Nemko GS, CB, CCC
EMI	FCC, CE, BSMI, CCC
Weight	System weight will vary according to configuration 27.2 kg (max)
Dimensions	87.3 (H) x 430 (W) x 710 (D) mm
Security features	Altos EasyDiagnostics - External warning LED - Power diagnostic LED Chassis intrusion alert Lockable door

On-board I/O connectors	Two PS/2 ports
	Two serial ports (DB9 and RJ-45)
	Three USB ports (one front-accessible)
	Two Ethernet (RJ-45) ports
	Two VGA ports (one front-accessible)

Model	Artikelnummer	Prijs inc. BTW	
<b>Altos R720</b> Altos R720, Rack 2U, Xeon QC E5405 2.0GHz/1333 MHz/12MB, 2x1GB FBD 667, ROMB (RAID 6 Support) + 512MB Cache, DVD writer, 2x146GB HDD, EURO power cable, no rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.R72D0.HS4	EUR 2466.00	
<b>Altos R720</b> Altos R720, Rack 2U, Xeon DC E5205 1.83GHz/1066 MHz/6MB, 2x1GB FBD 667, ROMB + 256MB Cache, no DVD, no HDD, EURO power cable, no rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.R72D0.030	EUR 1595.00	
<b>Altos R720</b> Altos R720, Rack 2U, Xeon QC E5405 2.0GHz/1333 MHz/12MB, 2x1GB FBD 667, ROMB (RAID 6 Support) + 512MB Cache, no DVD, no HDD, EURO power cable, no rack rail kit, no KB, no mouse, EasyBuild+ASM, 3 Year Warranty On Site Next Business Day	TT.R72D0.053	EUR 1958.00	
<b>Acer Garantie Uitbreiding</b> warranty 3Y on-site 4H onsite G7xx/R7xx (mon-fri. 09:00-18:00, call before 14:00, if later than 14:00 onsite next business morning)	SV.WSVAF.A04	EUR 869.00	

## Acer Altos R920

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- 64-bit en Quad-Core prestaties
- Missiekritieke betrouwbaarheid
- Eenvoudig te installeren en beheren

**Standaardconfiguratie**

Form Factor	Rack optimized server, 4U
Processor	Up to four quad core or dual core Xeon MP processor Front side bus 1066 Mhz Intel® Virtualization Technology Intel® HT technology Supports Intel® Extended Memory 64 technology
Number of processor	Two Dual or Quad Core CPU installed, up to 4 CPU max
Cache	According to CPU model: 4MB, 6MB, 8MB
Chipset	Intel® 7300 Chipset
Memory	Up to 128GB of ECC DDR2 667 MHz Fully Buffered DIMMs Up to 32 DIMM slots Standard configuration includes one memory board for up to 8 DIMM. Support for up to 4 memory board (32 DIMM) in maximum configuration. Memory Sparring technology Memory Mirroring technology Memory Mirroring and Sparring require specific memory configurations, verify on local Price List and with your local Acer representative.
Expansion slots	Seven PCI Express Slots Two hot-swappable PCI Express® x8 (x8 throughput) Two PCI Express® x8 (x8 throughput) Three PCI Express® x8 (x4 throughput)
Storage interface	Two integrated SATA 3 Gb/s ports Eight integrated SAS ports Embedded RAID option
RAID support	Integrated SAS software with RAID 0, 1, 10 support RAID activation key SAS hardware supporting RAID 0, 1, 5, 6, 10, 50, 60 (may be included in specific configurations) 512MB RAID Cache (may be included in specific configurations) RAID BBU (may be included in specific configurations)
Disk bays	eight hot-swappable 2.5" SAS HDDs Slim-type DVD-ROM, Slim DVD-Super Multi or DVD/CD-RW combo
Media bays	one free 5.25" bay for optional USB/SAS tape drive
Max Internal Storage	1.176TB SAS (8x 147GB SAS drives)
Network Interface	Integrated four-port Gigabit Ethernet
Power Supply	1570 W 1+1 hot-swappable, redundant power supply, 110/220 V
Hot Swap Component	Hard Disk Drives Redundant Power Supply Hotswap redundant fans Hot pluggable PCI slots
Systems management	Acer Altos Easydiagnostics Acer Altos Remote Management Card option kit Acer Altos Advanced Server Manager Acer Altos Easybuild
Floppy and CD	DVD slimline standard optional External USB 3.5" FDD
Cooling system	hot-swap redundant fan modules
Operating systems supported	Microsoft® Windows Server® 2003 Standard and Enterprise Edition Microsoft® Windows Server® 2003 Standard and Enterprise Edition (EM64T) Red Hat® Enterprise Server 5.0 Red Hat® Enterprise Linux® 5.0 (EM64T) SuSE® Linux Enterprise Server 10 SuSE® Linux Enterprise Server 10 (EM64T)
Safety	Nemko GS, UL/cUL, BSMI, CB
EMI	FCC Class A, CE, BSMI
Weight	41 kg - System weight will vary according to configuration. The weight indicated is for a typical configuration
Dimensions	173 x 445 x 699 mm (6.8 x 17.5 x 27.5 inches)
Onboard I/O connectors	5x USB connector (2 rear, 3 front) 2x Video port (1 front, 1 rear) 1x 9 pin serial port 4x network ports RJ-45
System Management	Acer Altos Easybuild 8.0 Acer Altos Advanced Server Manager 8.0 Acer Altos Remote Management Card option kit Acer Altos Easydiagnostics

Model	Artikelnummer	Prijs inc. BTW
<b>Altos R920</b> Altos R920, Rack 4U, 2x Xeon MP QC E7310 1.6GHz/1066/4MB, 2x1GB FBD, 1xMemory board, DVD slimline, SAS ROMB + 512MB + BBU, no HDD, 4X LAN Gbit, no Rack Kit, EURO power cable, no KB, no mouse, EasyBuild+ASM, 3 Years Warranty On Site Next Business Day	TT.R92E0.003	EUR 6529.00

## Acer Aspire easyStore Home Server

**Target User**

- Thuis/Privégebruikers
- Professional en Kleinzakelijke Oplossingen

**Key Selling Points**

- Media sharing
- PC backup
- PC Restore
- Server management
- Storage expansion
- Folder protection
- Remote access
- Network access
- One-touch USB copy
- DLNA Certified™
- Lights out

**Standaardconfiguratie**

Processor	Intel® Atom™ Processor 230
Chipset	Intel® 945GC Express Chipset + ICH7R
Disk Drives	Up to 4x 3.5" hot-swappable SATA HDDs One or two 640GB HDD installed. The number and size of pre-installed HDD(s) can change according to different configuration or geography OS pre-loaded HDD does not support hot-swapping. The hard drive containing the operating system cannot be hot-swapped. Doing so will cause a system crash. If you want to move the drive to another bay the system needs to be powered off. Acer is not responsible for problems/damage caused when performing such a procedure.
Max. HDD Capacity	4 TB of maximum internal storage capacity. May vary if new HDD sizes are made available. Optimal performance is only assured with Acer-approved components. Installation of other components is at your own risk.
Flash ROM	256 MB flash
RAM	1 GB DDR2 667 MHz unbuffered SDRAM
Front I/O	1x USB 2.0 port
Rear I/O	1x RJ-45 LAN port, 4x USB 2.0 ports, 1x e-SATA port, 1x recovery/reset pinhole
Networking	Gigabit Ethernet
Dimensions	200 (W) x 180 (L) x 212 (H) mm
Weight	4.5 kg (without HDD) 5.1 kg (with 1 HDD) System weight varies according to configuration. The weight quoted is for a typical configuration.
Power Supply	200 W, 100-240 V AC
EMC/Safety	Nemko (CB & Bauart), MET, CE, FCC, BSMI, CCC, VCCI
Internet Security	McAfee® Total Protection™ Service (6-month free trial)
System OS	Microsoft® Windows® Home Server
Network Client OS	Windows Vista® Windows® XP
Warranty	Standard Warranty: one year Carry-in. Warranty terms can differ according to local regulations. Optional warranty may also be available in selected countries.

Model	Artikelnummer	Prijs inc. BTW
<b>Acer Aspire easyStore Home Server</b> Aspire easyStore Home Server, English preload. Windows Home Server, Atom 230, 1x1GB DDR2 800, 1x640GB HDD. UK, EUR, CH power cable. 1 Year Carry-In Warranty	TS.R360W.011	EUR 461.00
<b>Acer Aspire easyStore Home Server</b> Aspire easyStore Home Server, English preload. Windows Home Server, Atom 230, 1x1GB DDR2 800, 2x640GB HDD. UK, EUR, CH power cable. 1 Year Carry-In Warranty	TS.R360W.012	EUR 528.00

## Aspire easyStore

**Target User**

- Thuis/Privégebruikers
- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen

**Key Selling Points**

- ORGANISEER UW DIGITALE THUISBIBLIOTHEEK
- BESCHERM UW KOSTBARE HERINNERINGEN
- DEEL UW FOTO'S EN MUZIEK MET FAMILIE EN VRIENDEN
- EENVOUDIGE INTEGRATIE MET UW NETWERK, UW WONING VOORBIJ
- HET HART VAN DE NIEUWE DIGITALE WONING

**Standaardconfiguratie**

Processor	Marvell® 88F5281
Hard disk drive	SATA
RAID level support	Levels 0, 1, 5, JBOD
Disk drives	4 x Serial ATA Hard Drives
Raw capacity	1 or 2 TB
I/O ports	One RJ-45 port
Networking	10/100/1000 Ethernet, auto MDI/MDIX WLAN: 802.11b/g
Network protocol	FTP/SMB
Network service protocols	DHCP client/server TCP/IP SMB SMTP HTTP/HTTPS DLNA HNV1 NTP/SNTP
Audio file support	MP3, WAV/PCM, WMA, AC3/AAC, OGG, AIF/AIFF
Video file support	VOB, AVI, MPEG2, MPEG4, WMV9
Playlist support	M3U, PLS, WPL, RMP, ASX
Image file support	JPG, BMP, GIF, TIF, PNG
System OS	Embedded Linux®
Network Client OS	Windows Vista® Windows® XP Windows® 2000 Linux® Mac OS® X
Dimensions	16 x 18 x 21 cm
Weight	5.3 kg
Power supply	19 V 150 W external power adapter

Model	Artikelnummer	Prijs inc. BTW
<b>Aspire easyStore 2TB _EU</b> Aspire easyStore 2 Terabyte, Wireless, Euro Power Cable, 1 Years Carry-In Warranty	ST.EASYA.2TB	EUR 594.00

## Altos easyStore

**Target User**

- Professional en Kleinzakelijke Oplossingen
- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- Bestanden delen
- Automatische client back-up en remote systeemherstel
- Geavanceerde gegevensbescherming
- Snapshot back-up
- Eenvoudige set-up
- Eenvoudig te beheren
- Stille, energiebesparende NAS en toch groot in capaciteit
- Ingebouwde DHCP- en FTP-server
- Intel XScale Processor

**Standaardconfiguratie**

Processor	Intel® 80219 IOP 600MHz
Max Speed	600 MHz
System Memory	DDR-SDRAM 256MB
Embedded OS	Intel® 8MB NOR Flash
Storage Capacity	Up to 2TB (4x SATA HDD)
Hard Disk Drive	4 Serial ATA , SATA I / II , Intel® 31244
RAID levels	RAID 0, 1, 5, 10, and JBOD
File Format Protocol	CIFS/SMB/NFS
Network Controller	Intel® i82541 Gigabit Ethernet
Bandwidth	1Gb
USB 2.0 x2	FAT/FAT32 file format for flash Disk
Client OS Support	Windows 2000/XP/20003, UNIX, Mac 7.X and later, Linux
Client Backup	Yes
Client Recovery	Yes
No. of Client License	2 standard, up to 16 optional
Network Protocol	FTP, CIFS/SMB, NTFS
Network Service	DHCP Client/Server
Management Interface	Web GUI
Client Support Capabilities	Max. 64 Clients, Max. 16 Groups, Max. 32 Shared Folders
Shared Folder Access Control	user name or group level access authentication
System Fan	1 (92 x 92 x 25 mm)
Temperature, Ambient Operating	0 to 40 °C
Humidity, Ambient Operating	10 to 90 percent
Dimensions	11.5 x 24 x 21 cm
Weight	4.5 kg
Front Panel	Power Button x 1, Power LED x 1, LAN Connection LED x 1, LAN Active LED x 1, RAID Status LED x 1, System Status LED x 1
Back Panel	Reset Button x 1, Gigabit Ethernet (RJ45) Port x 1, USB 2.0 Port x 2, Power Socket x 1
Input	AC 115-230V @ 50-60 Hz
Output	220W
Compliance	CE/FCC Class B

Model	Artikelnummer	Prijs inc. BTW	
<b>Altos easyStore 2TB</b> Altos easyStore 2 Terabyte. NAS Box with 4x 500GB SATA 2 HDDs on Acer Hot Swap carrier. RAID 0,1,10,5 support, 256MB cache, 1x LAN ports, 2x USB connectors, 1x Client License DiskSafe Express Backup & Recovery. 3 Years Carry-In Warranty	ST.EASYS.2TC	EUR 869.00	
<b>Altos easyStore 3TB</b> Altos easyStore 3 Terabyte. NAS Box with 4x 750GB SATA 2 HDDs on Acer Hot Swap carrier. RAID 0,1,10,5 support, 256MB cache, 1x LAN ports, 2x USB connectors, 1x Client License DiskSafe Express Backup & Recovery. 3 Years Carry-In Warranty	ST.EASYS.3TC	EUR 1087.00	
<b>Altos easyStore 4TB</b> Altos easyStore 4 Terabytes. NAS Box with 4x 1TB SATA 2 HDDs on Acer Hot Swap carrier. RAID 0,1,10,5 support, 256MB cache, 1x LAN ports, 2x USB connectors, 1x Client License DiskSafe Express Backup & Recovery. 3 Years Carry-In Warranty.	ST.EASYS.4TD	EUR 1377.00	

## Altos Rack 1024

**Target User**

- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- Altos 1024 wordt volledig geassembleerd geleverd met alle benodigde componenten voor direct gebruik.
- Altos 1024 wordt standaard geleverd met afsluitbare, volledig geperforeerde voor- en achterdeuren die een optimale air flow bieden
- T-slots in het rack frame zijn geschikt voor variabele positionering van kabelbeheer, power distributie en andere accessoires. De top cover van het rack bevat een 3-delig aanpasbare kabeltoegang met brush-strip voor stofbescherming
- Meer dan 80% van het achterste deel is open, voor eenvoudige toegang tot de bekabeling zelfs als er diepe apparatuur in het rack zit
- Een mobiele plank verlengt de rack deur met 100mm voor meer portability, eenvoudigere kabeltoegang en verbeterde stabiliteit. De plank kan worden verwijderd voor gebruik op verhoogde computervloeren of om de laadcapaciteit van het rack te verhogen

**Standaardconfiguratie**

OVERALL HEIGHT WITH PLINTH	1300mm
OVERALL HEIGHT WITHOUT PLINTH	1200mm
EQUIPMENT MOUNTING HEIGHT	1067mm
OVERALL DEPTH WITH PLINTH	1100mm
OVERALL DEPTH WITHOUT PLINTH	1000mm
EQUIPMENT MOUNTING DEPTH	740mm
FREE SPACE IN FRONT OF EQUIPMENT	90mm
FREE SPACE BEHIND EQUIPMENT	90mm
OVERALL WIDTH	600mm
FREE AIRFLOW THROUGH MESH DOORS	63%

Model	Artikelnummer	Prijs inc. BTW
<b>Acer Altos Rack 1024 Basic</b> Altos 1024 Basic: 1x 24U Rack, 4x 19" Component Mounting Hole Extrusion, 2x Side Panel D1000, 2x Multifunctional Strut D1000, 2x Door with Lock (front & rear), 1x Top Cover with Cable Entry Installed with "BrushStrip", 1x Mobile Plinth D1100 with Cable Entry and Leveling Feet, 1x Complete Earthing set, 1x (50pcs) Cage Nut M5, 1x (50pcs) Oval Head Screw M5 with Washer, 1x (5pcs) Cable Routing Ring	SO.24U00.001	EUR 1726.00

## Altos Rack 1042

**Target User**

- Kleine en Middelgrote Ondernemingen
- Enterprises

**Key Selling Points**

- Altos 1042 wordt volledig geassembleerd geleverd met all vereiste componenten voor direct gebruik
- Altos 1042 wordt standaard geleverd met afsluitbare, volledig geperforeerde voor- en achterdeuren die de air flow optimaliseren
- T-slots in het rack frame zijn geschikt voor variabele positionering van kabelbeheer, power distributie en andere accessoires. De top cover van het rack bevat een 3-delige, aanpasbare kabeltoegang met borstel strip voor stofbescherming
- Samenstelling is geschikt voor eenvoudige toegang tot de kabels ook met zeer diepe componenten
- Een mobiele plank verlengt de rack deur met 100mm die de draagbaarheid verbetert, toegang tot de kabels vereenvoudigt en de stabiliteit verbetert. De plank kan worden verwijderd voor gebruik op verhoogde vloeren of om het laadvermogen van het rack te verhogen

**Standaardconfiguratie**

OVERALL HEIGHT WITH PLINTH	2100mm
OVERALL HEIGHT WITHOUT PLINTH	2000mm
EQUIPMENT MOUNTING HEIGHT	1867mm
OVERALL DEPTH WITH PLINTH	1100mm
OVERALL DEPTH WITHOUT PLINTH	1000mm
EQUIPMENT MOUNTING DEPTH	740mm
FREE SPACE IN FRONT OF EQUIPMENT	90mm
FREE SPACE BEHIND EQUIPMENT	90mm
OVERALL WIDTH	600mm
FREE AIRFLOW THROUGH MESH DOORS	63%
LOAD RATING WITH PLINTH	300kg static
LOAD RATING WITHOUT PLINTH	600kg static
EQUIPMENT MOUNTS	19" cage nut mounts to IEC 297-3
IP RATING	IP20
TESTS	earthing to VDE 0100 P.540 vibration test to MIL-STD 810 E IP test to DIN 40 050 / IEC 529
BASIC FRAME MATERIAL	aluminium extrusion / casting
PANEL MATERIAL	Sheet steel, powder coated RAL 7021 dark grey

Model	Artikelnummer	Prijs inc. BTW
<b>Acer Altos Rack 1042 Basic</b> Altos 1042 Basic: 1x 42U Rack, 4x 19" Component Mounting Hole Extrusion, 2x Side Panel D1000, 2x Multifunctional Strut D1000, 2x Door with Lock (front & rear), 1x Top Cover with Cable Entry Installed with "BrushStrip", 1x Mobile Plinth D1100 with Cable Entry and Leveling Feet, 1x Complete Earthing set, 1x (50pcs) Cage Nut M5, 1x (50pcs) Oval Head Screw M5 with Washer, 1x (5pcs) Cable Routing Ring	SO.42U00.001	EUR 1755.00